




ETL SINAR SOLUTIONS SDN BHD (1344715-H)

10-G, Jalan LP 7/5B, Taman Lestari Perdana, 43300 Seri Kembangan, Selangor.
Tel : 018-3970397 www.etlss.com.my

ETL 12-port industrial din-rail mount splicing modular panels are designed for either to support direct termination or fusion splicing. Fiber Optic Distribution Box Termination Box is used to provide a flexible platform to address the multitude of applications that exist in industrial installations. Easy to install and is capable of being mounted directly to standard electrical junction boxes



MODEL
ETL-19-4U-DIN-SPLICE-MODULER-SC

MODEL:
ETL-19-4U-DIN-SPLICE-BOX-SC



+6016-3618461

etlsinarsolutions@gmail.com www.etlss.com.my +6016-3618461



Structure and specifications

Items	unit	Details
FTB Size		
ETL-19-4U-DIN-SPLICE-MODULER-SC	(MM)	145/130/35
ETL-19-4U-DIN-SPLICE-BOX-SC		120/120/35
Material		Metal
Accommodates	(Pc)	Max 12 Port
Fiber adaptor	Port	SC/ST/FC/E2000-APC
entry cables		Cable grand
exit cables	mm	Max diameter 16-20mm
Weight	Kg	0.88
Application		Din rail
Temperatures	C	Temperatures:-40C -- 70C

