

1. PrimeStar Server Overview

PrimeStar is a provider of network infrastructure products specializing in:

- Fiber optic connectivity solutions
- Structured cabling systems
- Telecommunication cabinets & ODFs
- Server racks and accessories
- Indoor & outdoor enclosure systems

The brand focuses on high-reliability components designed for ICT, data center, and telco environments.

2. Product Range

PrimeStar supplies a full line of server and network infrastructure equipment:

A. Server & Network Cabinets

- Indoor metal racks (6U–42U)
- Wall-mounted and floor-standing types
- Various depth options (300–1000 mm)
- Ventilated and non-ventilated doors
- Optional fan units, PDU, cable trays

B. Fiber Optic Solutions

- Fiber patch cords (LC, SC, FC, ST, E2000, APC/UPC)
- Pigtails and adapters
- Indoor/outdoor ODF wall-mounted boxes
- Fiber termination boxes compliant with ITU standards
- FTTH patch panels & splice modules

C. Copper Structured Cabling

- Cat5E, Cat6, Cat6A patch cords
- UTP/FTP cables
- Patch panels & keystone jacks

3. Server Rack Series

Below is the PrimStar Rack System (PRS) coding structure:

PRS Series Format

PRS-[Size U][Width mm][Depth mm]-(I/O)

- I = Indoor
- O = Outdoor

Example

- PRS-9U5550-I (Indoor)
- Former model: ETL-9U6032-P

Standard Sizes Available

- 6U / 300 mm depth
- 9U / 320–550 mm depth
- 12U / 450–600 mm depth
- 22U / 600–800 mm depth
- 42U / 600–1000 mm depth

5. Quality & Compliance


PrimStar products meet:

- ISO/IEC 11801
- ITU-T fiber termination standards
- RoHS & REACH compliant materials
- *Malaysia SIRIM compliant*



Introduction to the 9U wall mounted server rack with easy access top and bottom. The dynamic Rack offerings are industry-standard 19-inch server cabinets that are designed for high availability server environments. With a depth of 500 mm this racks offer expansive rear channels with tool-less button mounts for virtually effortless.

Features:



| Structure and Technical Specifications | Y/N | Remark |
|---|-----|-------------------------|
| Size equipment rack POD | | 9U/500/550)mm |
| Thickness & size | | 1.2mm [-/+2mm] |
| 4 points of 13A socket | N | Optional |
| 2 nos of cooling fan | N | Optional |
| Cable Management 1U | Y | |
| Perforated front and rear doors | Y | Optional/ acrylic glass |
| Removable side panels | Y | |
| Anti-theft and anti-vandalism and locked. | Y | |
| Ventilation fan | N | 2Unit [Ac240v] |
| Local Manufacturer | Y | Malaysia |
| Product years warranty | | 3year above |

Product codes – ordering information

| Product Code | Size (U) | Width x Depth (mm) | Environment | Description / Notes |
|--------------------------------------|----------|--------------------|-------------|--------------------------------------|
| PRS-9U5550-I | 9U | 550 x 500 | I – Indoor | Current standard model |
| Former Model: ETL-9U6032-P | 9U | 550 x 500 | P – Indoor | <i>Discontinued / replaced model</i> |

Code Format Breakdown:

- **PRS** = Product series
- **9U** = Rack unit size
- **5550** = Width 550mm / Depth 500mm
- **I** = Indoor (O = Outdoor)

